

CROWELL & MORING, LLP
Intellectual Property Dept.
P.O. Box 14300
Washington, DC 20044-4300
(202) 624-2500

TRANSMITTAL MESSAGE/COVER SHEET

Date: July 16, 2002

PLEASE DELIVER THE FOLLOWING PAGES TO:

ATTN: Examiner Tran N. Nguyen

Company/Firm: USPTO - Group Art Unit 2834

Fax No.: 703.305.1341

Pages: 4

Re: U.S. Serial No. 09/400,437
Attorney Docket: 381NP/48224

From: Jeffrey D. Sanok

Firm: Crowell & Moring, LLP
Intellectual Property Dept.

Fax No.: (202) 628-8844

MESSAGE: As requested, faxed herewith are the pending claims in U.S.
application serial no. 09/400,437 (Attorney Docket No.
381NP/48224).

THIS MESSAGE IS INTENDED FOR THE USE OF THE INDIVIDUAL OR ENTITY TO WHICH IT IS ADDRESSED AND MAY CONTAIN INFORMATION THAT IT IS PRIVILEGED, CONFIDENTIAL AND EXEMPT FROM DISCLOSURE UNDER APPLICABLE LAW. IF THE READER OF THIS MESSAGE IS NOT THE INTENDED RECIPIENT OR THE EMPLOYEE OR AGENT RESPONSIBLE FOR DELIVERING THE MESSAGE TO THE INTENDED RECIPIENT, YOU ARE HEREBY NOTIFIED THAT ANY DISSEMINATION, DISTRIBUTION, OR COPYING OF THIS COMMUNICATION IS STRICTLY PROHIBITED. IF YOU HAVE RECEIVED THIS COMMUNICATION IN ERROR, PLEASE NOTIFY US IMMEDIATELY BY TELEPHONE (COLLECT), AND RETURN THE ORIGINAL MESSAGE TO US AT THE ABOVE ADDRESS VIA U.S. POSTAL SERVICE. THANK YOU.

Attorney Docket: 381NP/48224
U.S. Serial No. 09/400,437

PENDING CLAIMS 1-6 and 9-11

1. A rotary electric machine comprising a stator having a stator core wound with stator windings; and a rotor having a rotatable rotor core arranged opposite to said stator core through a gap, wherein

said rotor core has a number of magnetic poles corresponding to a plurality of projecting poles arranged on a side of said gap and along a circumferential direction of said rotor core and a plurality of rotor yokes, each of said rotor yokes forming a magnetic path for conducting magnetic flux of adjacent ones of said projecting poles, said rotor core being divided in the circumferential direction by the number of magnetic poles of said rotor core into divided rotor core portions, adjacent ones of said divided rotor core portions forming a respective one of said magnetic poles.

2. A rotary electric machine according to claim 1, wherein a position of said division is at each middle position of a width in the circumferential direction of said projecting poles.

3. A rotary electric machine comprising a stator having a stator core wound with stator windings; and a rotor having a rotatable rotor core arranged opposite to said stator core through a gap, wherein

said rotor core has a number of magnetic poles and respectively comprises a plurality of permanent magnets arranged and embedded therein on a side of said gap and along a circumferential direction of said rotor core and a plurality of rotor yokes, each of said rotor yokes forming a magnetic path for conducting magnetic flux of adjacent ones of said permanent magnets, said rotor core being divided in the circumferential direction by the number of magnetic

Attorney Docket: 381NP/48224
U.S. Serial No. 09/400,437

poles of said rotor core into divided rotor core portions, adjacent ones of said divided rotor core portions forming a respective one of said magnetic poles.

4. A rotary electric machine according to claim 3, wherein a position of said division is at each position between the poles of said permanent magnets.

5. A rotary electric machine according to claim 1, wherein said rotor core is made of a different material from a material of said stator core.

6. An electric vehicle comprising a battery for supplying electric power; a rotary electric machine for outputting drive torque to drive the vehicle by said supplied electric power; and a controller for controlling said drive torque, wherein

said rotary electric machine comprises a stator having a stator core wound with stator windings; and a rotor having a rotatable rotor core arranged opposite said stator core through a gap, and said rotor is formed of a rotor core divided in a circumferential direction of said rotor core in a unit forming each magnetic pole of said rotor core and a holding member having an I-shaped cross section for holding said rotor core, said holding member having an I-shaped cross section being disposed an inner peripheral side of said rotor core in order to lengthen a driving distance per charge of said vehicle by reducing the vehicle weight.

9. A rotary electric machine according to claim 2, wherein said rotor core is made of a different material from a material of said stator core.

Attorney Docket: 381NP/48224
U.S. Serial No. 09/400,437

10. A rotary electric machine according to claim 3, wherein said rotor core is made of a different material from a material of said stator core.

11. A rotary electric machine according to claim 4, wherein said rotor core is made of a different material from a material of said stator core.